


Near Detector Physics Working Group Summary

Gallagher, Harris, Pearce

Let's Start With a Story...

Near Detector Physics Group MINOS Meeting September 2003, FNAL




Fine grained detector measures sub-relativistic particles, has good vertex resolution and tracking.



Near Detector Physics Group MINOS Meeting September 2003, FNAL


Q² distributions of 2-track samples (K2K)






Data from their 1 kt H₂O Near Detector and Monte Carlo do not agree.

Measurements in the SciFi detector allow them to break the distribution out into QE and non-QE components.



Near Detector Physics Group MINOS Meeting September 2003, FNAL

K2K was able to fit this data by using different M_{Δ} (1.02–1.10) for resonance



events and altering the QE/non-QE fraction by 0.93. Studied old BNL bubble checking for consistency.

Arie Bodek claims that the real problem is that all neutrino MC's use outdated form factors, in particular non-zero G_F^n .




FIG. 3. The G_{En} extracted from the C2 data (\diamondsuit). Also shown are the values obtained from double-polarization experiments, and the Galster parametrization with its extrapolation into the region not covered by previous experiments (dotted line).

Near Detector Physics Group MINOS Meeting September 2003, FNAL

Arie's Conclusion:

Can fix the Q2 dependence either way (by changing mA or using correct vector form factors). However the overall *cross sections will be 10-15% too high if one chooses wrong*

Although the story is not completely resolved there are several lessons:

Having different measurements in the near location sampling different energies / interaction processes ______ Debbie (beam changes) is important for MC tuning. High resolution _____ Hugh /Geoff devices are particularly valuable. (fine grained ND)

2. Old bubble chamber data is still important and useful. Costas

3. The need to maintain consistency with electron scattering results.




There are a fair number of spare components available after the completion of the CalDet runs. Could these possibly be used to good use in the near hall?

•What spares / leftovers exist?
Geoff Pearce /Gary Drake

•How could they be best used?

Dave Boehnlein / Hugh Gallagher

•What are the physics capabilities?






- Fundamental Physics Measurements?
 - Rates are too low
- Direct Relevance to Oscillation Analysis
 - Separation of v_e events based on clean topological cuts?
- Monte Carlo Confirmation
 - Detector is used as a vertex detector
 - Improved topological separation
 - Improved resolution

Usefulness is limited by the small mass and containment – incomplete kinematic coverage for all processes.



In a first iteration, did simulations in a detector comprised entirely of scintillator planes. Two obvious problems: small mass and limited containment.

Even with a fully active detector around $\frac{1}{4}$ of quasi-elastic events are single tracks.



Possible detector optimized for good tracking / topological discrimination as well as $\nu_{\rm e}$ identification.

30 planes/view alternating views X/Y
1.5 m upstream of the front face of the ND
44 kg / plane, 2.66 tons total

. .

	ρ (plane)	λ _l /plane	X _o /plane	dE/dx/plane
Scintillator	1.032 g/cm ³	0.012	0.024	2.52 MeV
MINOS	5.9 g/cm ³	0.16	1.52	31.5 MeV
FGND	2.38 g/cm ³	0.03	0.56	6.35 MeV





MINERVA MC: S. Boyd and D. Casper

MINERVA TOP VIEW

Run 0 Event 21 Int Type QE CC/NC 1 Mech. nu-n Vertex (9.3, 24.4,1570.0) PNEU 14 (0.0000,0.0000,3.7862,3.7862) PLEP 13 (0.3690,0.7069,3.3449,3.4403)








Fiducial volume is 0.33 tons.




MINERVA TOP VIEW


Run 0 Event 8 Int Type QE CC/NC 1 Mech. nu-n Vertex (-12.7, 7.2,1567.2) PNEU 12 (0.0000,0.0000,3.2250,3.2250) PLEP 11 (0.6900,-.2239,2.8427,2.9338)



1.4 GeV electron shower700 MeV proton

ν_e CC QEL








Event Rates: events/ yr in the FGND Fid Volume


	Elastic	CC QEL	NC INEL	CC INEL
v_{e}	30	80	250	840
ν_{μ}	3800	9735	19100	63700

Assumptions: Readout electronics for the entire 60 planes

No vetoing issues for this fiducial volume and analysis ...

Containment (ν_{μ} CC)






75% of the QEL produced muons are measured in the MINOS near detector.

60% overall for v_{μ} CC.





For this particular fiducial volume $\frac{1}{2}$ of coherent π^{0} have > 90% energy containment.



Cleanest sample for v_e identification are QEL-like events.


$$N_{e} = \oint \phi_{e} \sigma_{QEL} A^{e}_{Q} + \phi_{e} \sigma_{INEL} A^{e}_{Inel} dE$$

$$N_{m} = \oint \phi_{m} \sigma_{QEL} A^{m}_{Q} + \phi_{m} \sigma_{INEL} A^{m}_{Inel} dE$$

$$\frac{\phi_{e}}{\phi_{m}} = \frac{N_{e}}{N_{m}} \frac{\sigma_{QEL} A^{e}_{Q} + \sigma_{INEL} A^{e}_{Inel}}{\sigma_{QEL} A^{m}_{Q} + \sigma_{INEL} A^{m}_{Inel}}$$

~1. Differences are on the order of 10% and would need to be known to 30% For a 3% systematic uncertainty.

Uncertainty on this ratio from the beam group will be around 5% post-MIPP →





- Geoff did an inventory of available "warm spares"
 - Sufficient PMTs and bases (24 M64s)
 - Sufficient Alner boxes (16 CalDet and 3 ND spares)
 - DAQ spares sufficient to readout an extra master crate
 - Bottleneck is front end electronics, enough exists to read out 932 channels (36 planes)

	spares	required
Master Crate	1	1
Master	8	12
Minder	58	90
Menu+QIE	932	1440

Serious reservations were raised about the use of the ND electronics spares in this fashion:

- If this detector is actually useful, one wouldn't want to pull electronics out when needed
- Level of spares (10%) is based on a model for support that would be very

different from this.

Cost (not including development) is around \$250 / channel.



Not Crazy

- Independent, high resolution samples important for tuning MC
- Good e/h separation, π° measurement
- Possibility of a direct v_e measurement in several years running

Not Free

- Bare minimum cost using spares would be on order 100k\$
- More realistic is several 100k\$ for new electronics and some vetoing up front.



- Possibility put forward by D.Boehnlein, a variant of the outrigger concept presented by Vittorio in 2000.
- Put the steel back in to make 2 1 m³ outriggers, one upstream and one downstream.
- Coincidences could be used to measure high energy muons, which are more sensitive to horn shifts.

Nearly portable, could be moved with a crane or forklift.

Could be used as an adjustable muon telescope, moving one outrigger east/west could map out the angular distributions, and placing varying amounts of passive material in between could give a crude energy distributions.

Lack of space in the near hall is an issue.

Something for the beams systematic group to think about...




The NUMI kinematic range substantially overlaps that studied with high statistics in (e,e') experiments at SLAC, MIT, and the Jefferson Lab.

Comparing to electron data provides a strong constraint on many aspects of the simulation

- 1) Models for interaction processes
- 2) Nuclear effects
- 3) Combining different processes to obtain total cross section over all phase space.

The simplest comparisons can be done with Hydrogen/deuterium targets and allow us to Study (1) and (3) above in detail.




 σ_{tot} : σ_{res} for W<W_{cut}, σ_{DIS} for W>W_{cut} channel by channel tuning of DIS contributions (NEUGEN) duality-motivated approaches with new scaling variables (Bodek-Yang)



There is a proposal for a new Jefferson Lab experiment to measure inclusive electron scattering off of nuclear targets in the kinematic range important for NuMI. Improving knowledge for future neutrino experiments is the principle motivation.

Nailing down the vector part of the hadronic current in this kinematic regime gives a valuable constraint for neutrino models (Rein-Seghal for example).


An extension (5 extra days of beam time) to a planned experiment which will run in 2004.



Reconstruction / Tools


Costas Andreopoulos: Neural networks and event splitting.

Jim Musser: Track fitting and extrapolat into the spectrometer / spectrometer de-multiplexing. Exercises important elements of the reconstruction framework.



Tom Osiecki: NC / CC separation and shower finding in the near detector.

Peter Shanahan: Fast MC.



Randomized shower lengths from GMINO State of the shower lengths from GMINO Parametrized smearing of energies

